



# WILLIAMS VALVE

38-52 Review Ave • Long Island City, NY 11101  
1.800.221.1115 • wew@williamsvalve.com

## CRITICAL EMERGENCY SHUT OFF VALVES

### HOW TO ORDER - WILLIAMS FIGURE NUMBERS

A	B		C		D		E		F	
SIZE	VALVE TYPE		STEM / SEAT SURFACES		NACE		CLASS / ENDS		BODY SUFFIX	
	<b>PSL7</b>	ESOV with Lever and Spring and Fusible Link	<b>0</b>	Special Trim	<b>none</b>	Non-NACE	<b>none</b>	CL150 RF	<b>none</b>	ASTM A216 Grade WCB
	<b>APSL</b>	ESOV with Electric Auxillary components per WEW Data Sheet XX	<b>2</b>	410/Half hard-faced (Trim 8)	<b>N</b>	NACE MR 0175	<b>300</b>	CL300 RF	<b>LCC</b>	ASTM A352 Grade LCC
	<b>CPSL7</b>	ESOV with Pneumatic auxillairy components per WEW Data Sheet XX	<b>3</b>	410/Full hard-faced (Trim 5)			<b>600</b>	CL600 RF	<b>WC6</b>	ASTM A217 Grade WC6
			<b>6</b>	F316/F316 (Trim 10)			<b>150W</b>	CL150 BUTT WELD	<b>WC9</b>	ASTM A217 Grade WC9
			<b>62</b>	F316/Half hard-faced (Trim 12)			<b>300W</b>	CL300 BUTT WELD	<b>CF8M</b>	ASTM A351 Grade CF8M
			<b>63</b>	F316/Full hard-faced (Trim 16)			<b>600W</b>	CL600 BUTT WELD	<b>C5</b>	ASTM A217 Grade C5
							<b>600R</b>	CL600 RTJ	<b>C12</b>	ASTM A217 Grade C12
									<b>C12A</b>	ASTM A217 Grade C12A

#### CAST STEEL EMERGENCY SHUT OFF VALVE EXAMPLE:

3" CL300 ESOV, LCC Body and 410/Half hard faced trim, with Lever, Spring and Fusible Link - NACE - 3" PSL7-2 LCC

A	B	C	D	E	F
3"	PSL7	2	N	300	LCC