



WILLIAMS VALVE

38-52 Review Ave • Long Island City, NY 11101
 1.800.221.1115 • wew@williamsvalve.com

EMERGENCY SHUT OFF VALVES

HOW TO ORDER - WILLIAMS FIGURE NUMBERS

A	B		C		D		E		F	
SIZE	VALVE TYPE		TRIM		NACE		CLASS / CONNECTION		BODY SUFFIX	
	PL	ESOV with Lever and Adjustable Weight and Fusible Link	0	Special Trim	none	Non-NACE	none	CL150 RF	none	ASTM A216 Grade WCB
	PSL	ESOV with Lever and Spring and Fusible Link	2	API Trim 8	N	NACE MR 0175	300	CL300 RF	LCC	ASTM A352 Grade LCC
	CPSL	ESOV with Pneumatic Actuator, Spring, and Fusible Link	3	API Trim 5			600	CL600 RF	WC6	ASTM A217 Grade WC6
	APSL	ESOV with solenoid (NEMA 7), Spring, and Fusible Link	6	API Trim 10			150W	CL150 BUTT WELD	WC9	ASTM A217 Grade WC9
	MPSL	ESOV with Lever and Spring and Fusible Link and Electro Magnet and Optional Limit Switch	62	API Trim 12			300W	CL 300 BUTT WELD	CF8M	ASTM A351 Grade CF8M
			63	API Trim 16						

CAST STEEL EMERGENCY SHUT OFF VALVE EXAMPLE:

3" 150 ESOV, LCC Body, API Trim 12 NACE, with Lever, Spring and Fusible Link - 3" PSL-62N-600-LCC

A	B	C	D	E	F
3	PSL	62	N	600	LCC